

**webBikeWorld.com Torx Specifications**

Torx Size	Width Across "Points" (mm)	Maximum Torque Range	
		Foot-Pounds	Newton-Meters
T1	.81	.01 to .02	.02 to .03
T2	.93	.05 to .07	.07 to .09
T3	1.10	.10 to .13	.14 to .18
T4	1.28	.16 to .21	.22 to .28
T5	1.42	.32 to .38	.43 to .51
T6	1.70	.55 to .66	.75 to .90
T7	1.99	1.0 to 1.3	1.4 to 1.7
T8	2.31	1.6 to 1.9	2.2 to 2.6
T9	2.50	2.1 to 2.5	2.8 to 3.4
T10	2.74	2.7 to 3.3	3.7 to 4.5
T15	3.27	4.7 to 5.7	6.4 to 7.7
T20	3.86	7.74 to 9.37	10.5 to 12.7
T25	4.43	11.7 to 14.0	15.9 to 19
T27	4.99	16.6 to 19.8	22.5 to 26.9
T30	5.52	22.9 to 27.6	31.1 to 37.4
T40	6.65	39.9 to 48.0	54.1 to 65.1
T45	7.82	63.4 to 76.1	86 to 103.2
T50	8.83	97.4 to 117	132 to 158
T55	11.22	161 to 189	218 to 256
T60	13.25	280 to 328	379 to 445
T70	15.51	465 to 516	630 to 700
T80	17.54	696 to 773	943 to 1048
T90	19.92	984 to 1094	1334 to 1483
T100	22.13	1359 to 1511	1843 to 2048